

PRO T9H Series

SKU:- 2308-T982N-KH-11-4032



PRODUCT MAY VARY FROM THE ACTUAL PRODUCT


	Android 11.0
	RAM 4 GB
	ROM 32 GB



**Slim Frame Design
Thin & Lightweight
Panel**



**20 points touch and 10
points writing**



**Zero Gap
Bonding**



**Diverse
Connectivity
Multi-Interface
Support**

PROMARK STANDS FOR : PROGRESSIVE, PROACTIVE & PROFICIENT

PRO T9H Series

DISPLAY

Active Screen Size	65"	75"	86"
Model No.	PRO AT-65P	PRO AT-75P	PRO AT-86P
Panel Type	IPS	IPS	IPS
Response time	<4ms	<4ms	<4ms
Aspect Ratio	16:09	16:09	16:09
Resolution	3840×2160	3840×2160	3840×2160
Refreshing Frequency	120Hz	120Hz	120Hz
Brightness	450 cd/m2	500 cd/m2	600 cd/m2
Contrast Ratio	300000:1	300000:1	300000:1
Viewing Angle(V/H)	178°/178°	178°/178°	178°/178°
Display Colors	1.07B (10bit)	1.07B (10bit)	1.07B (10bit)
Life Time	≥120000H	≥120000H	≥120000H
Speakers	20W x2 (6Ω)	20W x2 (6Ω)	20W x2 (6Ω)

OPERATING SYSTEM

RAM	4GB
ROM	32GB
System Version	Android11.0
CPU	CPU: A55*4
GPU	Mali G52MP2

PROMARK TECHSOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE:
Plot No. F-22, Phase 8, Industrial Area,
Mohali Punjab- 160055

FACTORY:
Ludhiana Highway (NH-(95) Morinda By-Pass,
Village Madouli, Morinda, Distt. Ropar Punjab-140413

SALES OFFICE:
A-14, GF, Okhla Industrial
Area, Phase-2, New Delhi 110020

Branch Offices: Jammu and Kashmir, Chandigarh, Himachal Pradesh, Uttarakhand Haryana, Delhi, Rajasthan, UP-Lucknow & Bareilly, Bihar, Jharkhand, North East, Chhattisgarh, and Kolkata.

For any inquiries
contact us at:

www.promark.co.in



sales@promark.co.in



1800 103 8878

PRO T9H Series

TOUCH SYSTEM

Sensing Type	IR
Touch Recognition	Fingers, pens, or other non-transparent objects.
Accuracy	±1mm
Touch Points	20 points touch and 10 points writing

DIMENSION & WEIGHT

Dimension L*W*H (mm)	1488*897*88mm	1709*1020*88mm	1957*1160*100mm
Package Dimension (L*W*H)	1690(L)*210(W)*1060(H)	1920(L)*210(W)*1150(H)	2154(L)*230(W)*1354(H)
Net Weight	36.85kg ±1KG	47.65kg ±1KG	61.65kg ±1KG
Gross Weight	52KG±1KG	67KG±1KG	84KG±1KG

POWER CONSUMPTION

Power Supply	300W	430W	550W
Standby Power	<0.5W	<0.5W	<0.5W

I/O INTERFACE

Type-C*1; Public USB 3.0*2; HDMI Port*1; Touch USB3.0*1 Touch USB3.0*1; RS232*1; RJ45 (1000M) *2; HDMI 2.0 IN*2; USB TOUCH 2.0*1; Public USB 3.0*2; PC AUDIO IN*1; USB 2.0*1; VGA*1; USB Type C*1; DP*1; LINE OUT*1; OPTICAL OUT*1; HDMI OUT*1;

ENVIRONMENTAL CONDITIONS

Operation Temperature	0°-50°C
Operation Humidity	20%-80%

PROMARK TECHSOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE:
Plot No. F-22, Phase 8, Industrial Area,
Mohali Punjab- 160055

FACTORY:
Ludhiana Highway (NH-(95) Morinda By-Pass,
Village Madouli, Morinda, Distt. Ropar Punjab-140413

SALES OFFICE:
A-14, GF, Okhla Industrial
Area, Phase-2, New Delhi 110020

Branch Offices: Jammu and Kashmir, Chandigarh, Himachal Pradesh, Uttarakhand Haryana, Delhi, Rajasthan, UP-Lucknow & Bareilly, Bihar, Jharkhand, North East, Chhattisgarh, and Kolkata.

For any inquiries
contact us at:

www.promark.co.in



sales@promark.co.in



1800 103 8878