

T9H Series



PRODUCT MAY VARY FROM THE ACTUAL PRODUCT


	Android 13.0
	RAM 8 GB
	ROM 128 GB



Slim Frame Design
Thin & Lightweight
Panel



**20 points touch and 10
points writing**



**Zero Gap
Bonding**



**Diverse
Connectivity
Multi-Interface
Support**

PROMARK STANDS FOR : PROGRESSIVE, PROACTIVE & PROFICIENT

T9H Series

DISPLAY

Active Screen Size	65"	75"	86"
Model No.	PRO AT-65P	PRO AT-75P	PRO AT-86P
Panel Type	IPS	IPS	IPS
Response time	<4ms	<4ms	<4ms
Aspect Ratio	16:09	16:09	16:09
Resolution	3840×2160	3840×2160	3840×2160
Refreshing Frequency	120Hz	120Hz	120Hz
Brightness	450 cd/m2	500 cd/m2	600 cd/m2
Contrast Ratio	30000:1	30000:1	30000:1
Viewing Angle(V/H)	178°/178°	178°/178°	178°/178°
Display Colors	1.07B (10bit)	1.07B (10bit)	1.07B (10bit)
Life Time	≥ 1,20,000H	≥ 1,20,000H	≥ 1,20,000H
Speakers	20W x2 (6Ω)	20W x2 (6Ω)	20W x2 (6Ω)

OPERATING SYSTEM

RAM	8 GB
ROM	128 GB
System Version	Android 13.0
CPU	QuadCore A55*4
GPU	Mali G52MP2

PROMARK TECHSOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE:
Plot No. F-22, Phase 8, Industrial Area,
Mohali Punjab- 160055

FACTORY:
Ludhiana Highway (NH-(95) Morinda By-Pass,
Village Madouli, Morinda, Distt. Ropar Punjab-140413

SALES OFFICE:
A-14, GF, Okhla Industrial
Area, Phase-2, New Delhi 110020

Branch Offices: Jammu and Kashmir, Chandigarh, Himachal Pradesh, Uttarakhand Haryana, Delhi, Rajasthan, UP-Lucknow & Bareilly, Bihar, Jharkhand, North East, Chhattisgarh, and Kolkata.

For any inquiries
contact us at:

www.promark.co.in



sales@promark.co.in



1800 103 8878

T9H Series

TOUCH SYSTEM

Sensing Type	IR
Touch Recognition	Fingers, pens, or other non-transparent objects.
Accuracy	±1mm
Touch Points	20 points touch and 10 points writing

DIMENSION & WEIGHT

Dimension L*W*H (mm)	1484.6 X 903.08 X 87.21	1706.76 x 1027.32 x 87.31	1952.96 X 1167.77 X 87.18
Package Dimension (L*W*H)	1630 x 220 x 1050 mm	1860 X 220 X 1160 mm	2120 X 220 X 1325 mm
Net Weight	45 kgs ±1 kg	58 kg ±1 kg	85 kg ±1 kg
Gross Weight	56 kg ± 1 kg	68 kg ± 1 kg	98 kg ± 1 kg

POWER CONSUMPTION

Power Supply	250W	280W	350W
Standby Power	<0.5W	<0.5W	<0.5W

I/O INTERFACE

FRONTS PORTS- USB Type-C X 1; USB 3.0 X 2; USB Touch Type-B X 1; HDMI In X 1
REAR PORTS - USB Type-C X 1; USB 3.0 X 2, USB 2.0 X 1; USB Touch Type-B X 1; HDMI In X 1; DP IN X 1;
RS232 X 1; SPDIF Out X 1; Audio Out X 1; Audio In X 1; HDMI Out X 1; RJ45 In x 1; RJ45 Out X 1; VGA X 1

ENVIRONMENTAL CONDITIONS

Operation Temperature	0°-50°C
Operation Humidity	20%-80%

PROMARK TECHSOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE:
Plot No. F-22, Phase 8, Industrial Area,
Mohali Punjab- 160055

FACTORY:
Ludhiana Highway (NH-(95) Morinda By-Pass,
Village Madouli, Morinda, Distt. Ropar Punjab-140413

SALES OFFICE:
A-14, GF, Okhla Industrial
Area, Phase-2, New Delhi 110020

Branch Offices: Jammu and Kashmir, Chandigarh, Himachal Pradesh, Uttarakhand Haryana, Delhi, Rajasthan, UP-Lucknow & Bareilly, Bihar, Jharkhand, North East, Chhattisgarh, and Kolkata.

For any inquiries
contact us at:

www.promark.co.in



sales@promark.co.in



1800 103 8878